



MATERIAL SAFETY DATA SHEET

B-100 BUTYL RUBBER SEALANT

Section One

PRODUCT INFORMATION

Manufacturer's Name: ADCO Products, Inc. Business Phone No: 1-517-764-0334
 Manufacturer's Address: 4401 Page Ave., P.O. Box 457 Emergency Phone No: 1-800-424-9300
 Michigan Center, MI 49254 (CHEMTREC)
 Product Name: **B-100 Butyl Rubber Sealant**
 Proper Shipping Name: Adhesive, containing flammable liquid, 3, UN1133, PG II

Section Two

HAZARDOUS INGREDIENTS INFORMATION

<u>Chemical Name</u>	<u>CAS #</u>	<u>% by Weight</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>
Aliphatic Hydrocarbon Solvent	8052-41-3	10%-20%	100 ppm	500 ppm

Section Three

PHYSICAL AND CHEMICAL DATA

Appearance & Odor: Paste available in various colors with aliphatic hydrocarbon odor
 Physical State: Paste Boiling Point: 352°F
 Specific Gravity (water = 1): 1.32 Evaporation Rate (n-butyl acetate = 1): 0.12
 Percent Volatiles: 10-20 Solubility in Water: 0.5%
 Vapor Pressure: 5 mm Hg @ 78°F, 26°C Vapor Density (air = 1): 5.0
 Percent Solids (by weight): 80-90 Melting Point: NA
 VOC Content: 248 grams/liter = 2.07 lbs/gallon

Section Four

FIRE & EXPLOSION HAZARD DATA

Flash Point: 106°F Method Used: Estimate based on the flash point of the most volatile component.

Flammable Limits: LEL: 0.5 UEL: 6.0

Proper Extinguishing Media: Foam, dry chemical or carbon dioxide. Water may be ineffective, but water should be used to keep fire-exposed containers cool.

Recommended Firefighting Procedures: Treat as a class "B" fire. Limit firefighting to those trained to do so. If a leak or spill has ignited, use water spray to disperse the vapors and to protect the men attempting to stop the leak. Minimize breathing gases, vapor, fumes or decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

Unusual Fire & Explosion Hazards: Vapors are heavier than air and may travel along the ground and be ignited by ignition sources distant from the handling point. Residue in "empty" containers may be explosive if exposed to an ignition source. To prevent fire or explosion from static accumulation and discharge, effectively ground the product transfer system.

Section Five**HEALTH HAZARD DATA**

Medical Conditions Aggravated by Exposure: Pre-existing eye, skin and pulmonary disorders may be aggravated by exposure to this product.

Primary Route of Entry:	Skin absorption	Yes
	Inhalation	Yes
	Ingestion	Yes
	Eye contact	Yes

Signs and Symptoms of Exposure:

Skin contact: Can cause redness, irritation, defatting, and dermatitis.

Inhalation: Prolonged inhalation of vapors may cause irritation of the respiratory tract. Intentional misuse by deliberately concentrating and inhaling vapor may be harmful or fatal.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

Eye contact: Can cause severe irritation, redness, tearing, blurred vision.

Emergency and First Aid Procedures:

On skin: Wash with soap and water. Get medical attention if irritation persists.

Inhaled: Remove affected person to fresh air, give oxygen or artificial respiration as necessary to assist breathing. Get medical attention.

Ingested: Do not induce vomiting. Get medical attention.

In eyes: Flush with large amounts of water, frequently flushing under the lids. Seek medical attention.

Acute Effects of Overexposure: Irritation, redness

Chronic Effects:(include all potential carcinogens present @ .1% or greater): None known

Carcinogenicity: NTP? No IARC Monographs? No OSHA regulated? No

Section Six**REACTIVITY DATA**

Stability: Stable

Conditions to Avoid: None known

Hazardous Decomposition Products: In the event of partial combustion, fumes, smoke, carbon monoxide, aldehydes and other decomposition products may be released.

Hazardous Polymerization: Will not occur

Incompatibility: None known

Section Seven**PRECAUTIONS FOR SAFE HANDLING AND USE**

Ventilation: General exhaust as needed to keep TLV below recommended levels if engineering or administrative controls are not adequate.

Personal Protective Equipment:

Respirator: For large spills or entry into enclosed small spaces with inadequate ventilation, a pressure demand, self-contained breathing apparatus is recommended. If engineering or administrative controls are not adequate to maintain solvent TLV below recommended levels, an appropriate respirator should be used in conjunction with a respirator use and fit training program.

Gloves: Buna-N, if needed

Eye Protection: Safety glasses with side shields if needed.

Other Protective Clothing/Articles: To prevent repeated or prolonged skin contact, wear impervious clothing and boots if contact is likely.

Work/Hygienic Practices: Minimize breathing vapor. Avoid prolonged or repeated contact with the skin. Remove contaminated clothing and launder before reuse. Cleanse skin thoroughly after contact, before work breaks and meals and at the end of the workday. Product is readily removed from the skin with waterless hand cleaners followed by washing thoroughly with soap and water.

Steps To Be Taken in Case Material is Released or Spilled: Eliminate all ignition sources. Control the source of the spill if it is safe to do so. Ventilate enclosed areas to prevent vapor accumulation. Restrict access by unauthorized personnel. Absorb spilled product with vermiculite or other absorbent material. Shovel or scoop into a sealable container for disposal.

Waste Disposal Method: If this product becomes a waste, it is considered a hazardous waste due to its ignitability. Dispose of in accordance with local, state and federal environmental and waste regulations.

Storage and Handling Procedures: Do not store or handle near an ignition source. Keep containers closed. Effectively ground the product transfer system to prevent fire or explosion from static discharge. Empty containers may contain residual product. Do not reuse containers unless properly reconditioned.

Section Eight**REGULATORY INFORMATION**

All components are included in the EPA Toxic Substance Control Act (TSCA) Chemical Substance Inventory.

If this product becomes a waste, it meets the criteria of a hazardous waste as defined under RCRA 40CFR261: Ignitability

Hazardous Materials Identification System (HMIS):

Health Hazard Rating: 1 CAUTION Irritation or minor reversible injury possible

Flammability Hazard Rating: 2 CAUTION Material must be moderately heated before ignition will occur.

Reactivity Hazard Rating: 0 Normally stable and will not react with water

Personal Protective Equipment: B Safety glasses and gloves

EPA SARA Title III hazard class (40CFR370): Acute Health Hazard
Chronic Health Hazard
Fire Hazard

EPA SARA Title III Section 313 (40CFR372): There are no listed toxic chemicals present in quantities greater than the *de minimis* level.

EPA SARA Title III (40CFR355): There are no components present in this product at a level which would require reporting.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

This product contains no listed substances, which the State of California has found to cause cancer, birth defects, or other reproductive harm, in a form which would require a warning under the statute.

Date of Preparation: January 4, 2010

Revision: 14 Supersedes MSDS Dated: May 24, 2007

THIS INFORMATION RELATES TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF OUR KNOWLEDGE AND BELIEF ACCURATE AND RELIABLE AS OF THE DATE COMPILED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. WE DO NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION NOR DO WE OFFER WARRANTY AGAINST PATENT INFRINGEMENT.